



Bodo Caspar Kielmann (Autor)

## **Färbung und Farbstabilisierung von Massivholz mit niedrigmolekularen Melamin- und Phenol- Kondensationsharzen**



<https://cuvillier.de/de/shop/publications/8043>

Copyright:

Cuvillier Verlag, Inhaberin Annette Jentsch-Cuvillier, Nonnenstieg 8, 37075 Göttingen,  
Germany

Telefon: +49 (0)551 54724-0, E-Mail: [info@cuvillier.de](mailto:info@cuvillier.de), Website: <https://cuvillier.de>



---

# Inhaltsverzeichnis

<b>Zusammenfassung .....</b>	<b>XIII</b>
<b>Abstract.....</b>	<b>XVII</b>
<b>Inhaltsverzeichnis .....</b>	<b>XXI</b>
<b>Abkürzungsverzeichnis .....</b>	<b>XXVII</b>
<b>Kapitel 1 – Einleitung.....</b>	<b>1</b>
1.1 Hintergrund.....	1
1.2 Holz.....	3
1.3 Holzaufkommen und -auswahl.....	6
1.4 Holzmodifizierung .....	10
1.5 Holzmodifizierung mit Polykondensationsharzen.....	14
1.5.1 Melamin-Formaldehydharz .....	14
1.5.2 Phenol-Formaldehydharz.....	20
1.6 Verwitterung und Färbung von Holz .....	27
1.6.1 Azo- und Säurefarbstoffe.....	29
1.6.2 Eisen-Tannin-Verbindungen.....	31
1.7 Farbstabilisierung durch transparente Beschichtungen.....	35
1.8 Zielsetzung und Fragestellung.....	39
1.9 Publikationsliste.....	40
<b>Kapitel 2 – Modification of three hardwoods with an N-methylol melamine compound     and a metal-complex dye .....</b>	<b>41</b>
2.1 Abstract .....	43
2.2 Introduction .....	43
2.3 Materials and methods .....	44
2.3.1 Wood and chemicals .....	44
2.3.2 NMM-dye treatment.....	45
2.3.3 Fixation of the dye .....	45
2.3.4 Colour measurements and nitrogen analysis .....	45
2.3.5 Light microscopy and SEM-EDX analysis .....	45
2.3.6 UV micro-spectrophotometry (UMSP).....	46
2.4 Results and discussion .....	46
2.4.1 Solution uptake and weight percent gain.....	46
2.4.2 Penetration of NMM-dye (BS) into the wood.....	47
2.4.3 Distribution of the dye in the cell wall .....	48
2.4.4 Topochemistry of NMM-dye-treated wood.....	48



2.5 Conclusion.....	53
<b>Kapitel 3 – Strength changes in ash, beech and maple wood modified with a N-methylol melamine compound and a metal-complex dye.....</b>	<b>55</b>
3.1 Abstract.....	57
3.2 Introduction.....	57
3.3 Materials and methods.....	58
3.3.1 Wood and chemicals.....	58
3.3.2 Wood Treatment.....	58
3.3.3 Mechanical properties.....	58
3.4 Results and discussion.....	59
3.5 Conclusions.....	62
<b>Kapitel 4 – Decay resistance of ash, beech and maple wood modified with N-methylol melamine and a metal-complex dye.....</b>	<b>65</b>
4.1 Abstract.....	67
4.2 Introduction.....	67
4.3 Materials and Methods.....	68
4.3.1 Wood and chemicals.....	68
4.3.2 Micro-organisms.....	69
4.3.3 NMM-dye treatment.....	69
4.3.4 White and brown rot testing.....	69
4.3.5 Soft rot testing.....	70
4.4 Results and discussion.....	70
4.4.1 White and brown rot decay.....	70
4.4.2 Soft rot decay.....	72
4.5 Conclusions.....	73
<b>Kapitel 5 – The effect of combined melamine-resin- colouring-agent modification on water related properties of beech-wood.....</b>	<b>75</b>
5.1 Abstract.....	77
5.2 Introduction.....	77
5.3 Material and Methods.....	78
5.3.1 Wood and chemicals.....	78
5.3.2 NMM resin and NMM resin-dye treatment.....	78
5.3.3 Fixation of chemical.....	79
5.3.4 Bulking, anti-shrink efficiency, maximum swelling.....	79
5.3.5 Equilibrium moisture content (EMC).....	79
5.3.6 Capillary water uptake.....	80
5.3.7 Micro-computed tomography.....	80



5.4 Results and Discussion.....	80
5.4.1 Weight percent gain and solution uptake .....	80
5.4.2 Bulking, anti-shrink efficiency, and maximum swelling ( $S_{wmax}$ ) .....	81
5.4.3 Equilibrium moisture content .....	82
5.4.4 Swelling at various relative humidities (RH) .....	84
5.4.5 Capillary water uptake.....	85
5.5 Conclusions .....	87
<b>Kapitel 6 – Application and artificial weathering performance of translucent coatings on resin-treated and dye-stained beech-wood.....</b>	<b>89</b>
6.1 Abstract .....	91
6.2 Introduction .....	91
6.3 Materials and methods .....	93
6.3.1 Wood specimens and chemicals .....	93
6.3.2 Modification of wood.....	93
6.3.3 Coating application .....	94
6.3.4 Drying time of finish .....	94
6.3.5 Water uptake.....	94
6.3.6 Artificial weathering and colour measurement.....	95
6.3.7 Adhesion strength and wood fracture.....	95
6.4 Results and discussion .....	96
6.4.1 Weight percent gain and solution uptake .....	96
6.4.2 Drying rate of finishes on wood.....	96
6.4.3 Capillary water uptake.....	98
6.4.4 Artificial weathering and colour change .....	99
6.4.5 Adhesion of finishes.....	102
6.5 Conclusion.....	105
<b>Kapitel 7 – Natural weathering performance and the effect of light-stabilizers in water-based coating formulations on resin-modified and dye-stained beech-wood .....</b>	<b>107</b>
7.1 Abstract .....	109
7.2 Introduction .....	109
7.3 Materials and methods .....	111
7.3.1 Wood specimens and chemicals .....	111
7.3.2 Modification of wood.....	111
7.3.3 Coating application .....	111
7.3.4 Natural weathering .....	112
7.3.5 Surface evaluation.....	112
7.3.6 Optical appearance .....	113
7.4 Results and discussion .....	113
7.4.1 Weight percent gain and solution uptake .....	113



7.4.2	Coatability of wood.....	113
7.4.3	Natural weathering .....	114
7.4.3.1	Mass changes .....	114
7.4.3.2	Formation of defects and cracks.....	115
7.4.3.3	Water uptake in course of weathering .....	117
7.4.3.4	Color change .....	118
7.5	Conclusion.....	121
<b>Kapitel 8 – Modification of wood with formulations of phenolic resin and iron-tannin-complexes to improve material properties and expand colour variety .....</b>		
8.1	Abstract .....	125
8.2	Introduction .....	125
8.3	Materials and methods .....	126
8.3.1	Wood specimens and chemicals .....	126
8.3.2	Modification of wood.....	127
8.3.3	Fixation of chemical.....	127
8.3.4	Cell wall bulking, anti-shrink efficiency, maximum swelling .....	127
8.3.5	Equilibrium moisture content (EMC) .....	128
8.3.6	Capillary water uptake.....	128
8.3.7	Artificial weathering .....	128
8.4	Results and discussion .....	129
8.4.1	Weight percent gain and solution uptake .....	129
8.4.2	Bulking, anti-shrink efficiency (ASE), and maximum swelling ( $S_{Wmax}$ ).....	129
8.4.3	Equilibrium moisture content .....	131
8.4.4	Artificial weathering and colour change .....	133
8.4.5	Capillary water uptake.....	134
8.5	Conclusion.....	135
<b>Kapitel 9 – Zusammenfassung der Ergebnisse und Diskussion.....</b>		
9.1	Verteilung der Modifizierungskemikalien.....	137
9.1.1	Makroskopische Verteilung.....	137
9.1.2	Mikroskopische Verteilung .....	141
9.1.3	Einfluss verschiedener Prozessparameter.....	143
9.2	Mechanische Holzeigenschaften .....	143
9.3	Dauerhaftigkeit und Mechanismen der Dauerhaftigkeitserhöhung.....	146
9.4	Feuchtebedingte Holzeigenschaften .....	151
9.4.1	Auswaschungsbeanspruchung und Fixierung.....	152
9.4.2	Sorptionsverhalten.....	153
9.4.3	Dimensionsstabilisierung.....	156
9.4.4	Kapillare Wasseraufnahme.....	160
9.5	Bewitterungsverhalten von farbmodifiziertem Holz .....	161



9.6 Farbstabilisierung durch Modifizierung und Beschichtung .....	165
9.7 Farbveränderung durch Modifizierung der Polykondensationsharze .....	169
<b>Kapitel 10 – Schlussbetrachtung und Ausblick .....</b>	<b>173</b>
<b>Literaturverzeichnis .....</b>	<b>177</b>
<b>Lebenslauf .....</b>	<b>207</b>