



Alireza Bastani (Autor)
Bondability of modified wood



<https://cuvillier.de/de/shop/publications/7282>

Copyright:
Cuvillier Verlag, Inhaberin Annette Jentsch-Cuvillier, Nonnenstieg 8, 37075 Göttingen,
Germany
Telefon: +49 (0)551 54724-0, E-Mail: info@cuvillier.de, Website: <https://cuvillier.de>



Table of content

1. Summary	1
2. Introduction	5
2.1. Wood and adhesion	5
2.1.1. Wood; a natural, renewable raw material.....	5
2.1.2. Furniture and building constructions.....	5
2.1.3. Adhesion background and theories.....	6
2.1.4. Influencing factors on bonding.....	8
2.1.5. Evaluation methods.....	9
2.2. Wood modification	11
2.2.1. Background, description and examples.....	11
2.2.2. Modified species.....	13
2.2.3. Furfurylation.....	13
2.2.4. Melamine treatment.....	15
2.2.5. Thermal modification.....	17
2.2.6. Phenol treatment.....	19
2.3. Bonding of modified wood and adhesives	19
2.3.1. Bonding of modified wood.....	19
2.3.2. Wood adhesives.....	21
2.3.2.1. EPI.....	23
2.3.2.2. PVAc.....	23



2.3.2.3. PU.....	24
2.3.2.4. PF.....	25
2.3.2.5. PRF.....	26
2.4. Aim of Study.....	26
2.5. Evaluation methods used in this research.....	28
2.5.1. Evaluation of the wood surface and water related properties.....	28
2.5.1.1. Capillary water uptake.....	28
2.5.1.2. Contact angle measurement.....	30
2.5.1.3. Surface energy of the wood.....	31
2.5.2. Optical evaluation.....	32
2.5.2.1. Light and fluorescence microscopy.....	32
2.5.2.2. X-ray micro-computed tomography.....	35
2.5.3. Evaluation of mechanical properties.....	37
3. Results and discussion.....	38
3.1. Evaluation of the effects of phenol formaldehyde modification of the beech wood on its bonding performance.....	38
3.2. Water uptake and wetting behaviour of furfurylated, N-methylol melamine modified and thermally modified wood.....	39
3.3. Gross adhesive penetration in furfurylated, N-methylol melaminemodified and thermally modified wood.....	41
3.4. Study of adhesive bondlines in modified wood with fluorescence microscopy and X-ray micro-computed tomography.....	44



3.5. Shear strength of furfurylated, N-methylol melamine and thermally modified wood bonded with three conventional adhesives.....	46
3.6. Effect of open assembly time and equilibrium moisture content on the penetration of polyurethane adhesive into thermally modified wood.....	48
3.7. Development of bonding strength of modified birch veneers during adhesive curing.....	51
4. Conclusions and further studies.....	53
5. References.....	56
6. Publications.....	64